Learn How to Count Rows Based on Value in Google Sheets: A Step-by-Step Guide with Examples

Authored by

Mohammed looti

October 31, 2025

RECOMMENDED CITATION

Mohammed looti (2025). *Learn How to Count Rows Based on Value in Google Sheets: A Step-by-Step Guide with Examples*. PSYCHOLOGICAL STATISTICS. Retrieved from https://statistics.arabpsychology.com/?p=7245

Mastering data manipulation is essential when working with large datasets, and one of the most fundamental tasks is accurately counting entries based on specific conditions. This tutorial details three robust methods available in Google Sheets that allow you to efficiently count rows containing a value, lacking a value, or matching a precise criterion. Understanding these techniques is crucial for effective data analysis and reporting.

Methodology Overview: Essential Counting Formulas

To calculate the total number of rows that satisfy a particular condition within a designated range, we utilize Google Sheets' built-in counting functions. The primary functions employed for conditional counting are **COUNTIF** and **COUNTBLANK**. Each formula serves a distinct purpose, providing flexibility depending on whether you are looking for presence, absence, or specificity of data.

We will examine three distinct approaches to counting rows, ensuring you can tailor the solution to your precise data requirements. Below is a summary of the formulas we will explore:

Method 1: Count Rows with Any Value (Non-Blank Cells) - Uses the **COUNTIF** function with a specific non-empty criterion.
Method 2: Count Rows with No Value (Blank Cells) - Uses the dedicated **COUNTBLANK** function.
Method 3: Count Rows with Specific Value - Uses the versatile **COUNTIF** function to match an exact numerical or text entry.

The following formulas demonstrate the basic syntax for each method, applied to the hypothetical range `A1:A10`:

Method 1: Counting Cells That Are Not Empty

To determine the number of rows that contain any data--meaning they are **not blank**--we leverage the `COUNTIF` function combined with the not-equal-to operator (`<>`). When used within `COUNTIF`, the criterion `"<>"` instructs the formula to count every cell in the specified range that is not empty. This is an excellent way to quickly assess data completeness.

=COUNTIF(A1:A10, "<>")

Method 2: Counting Cells That Are Completely Empty

Conversely, if the goal is to identify how many rows are missing data, the **COUNTBLANK** function provides a direct and simple solution. This function takes only one argument--the range--and returns the count of cells that are absolutely empty. This is highly useful for data cleaning and

identifying gaps in information.

=COUNTBLANK(A1:A10)

Method 3: Counting Cells That Match an Exact Value

When you need to count occurrences of a specific data point, such as a score, category, or identifier, the **COUNTIF** function is utilized with a literal value as the criterion. In the example below, the formula counts how many rows within the specified range contain the exact value `50`. Remember that the criterion must be enclosed in double quotes if it is a string or a numerical value being treated as a condition.

=COUNTIF(A1:A10, "50")

To illustrate the practical application of these counting methods, we will use the following sample dataset in Google Sheets, focusing on the data contained in the "Points" column (Column B):

	A	B	C	D
1	**Player**	**Points**		
2	A	6		
3	B	8		
4	C	8		
5	D			
6	E	8		
7	F	15		
8	G			
9	H	15		
10	I			
11	J	17		
12				
13				
14				
15				
16				

Example 1: Counting Rows with Any Value (Non-Blanks)

In this first scenario, our objective is to determine the total number of entries that successfully recorded a score in the "Points" column. We need to count every row in the range `B2:B11` that

contains a numerical or text value, effectively excluding any empty cells. This helps us understand how many data points were actually collected.

We achieve this by applying the `COUNTIF` function with the non-equality operator (`<>`). This function is designed specifically to count cells that meet a single specific condition across a range.

=COUNTIF(B2:B11, "<>")

The following screenshot demonstrates the implementation of this formula within the sheet:

D2 | fx | =COUNTIF(B2:B11, "<>")

	A	B	C	D	E
1	**Player**	**Points**		**Rows with Any Value**	
2	A	6		7	
3	B	8			
4	C	8			
5	D				
6	E	8			
7	F	15			
8	G				
9	H	15			
10	I				
11	J	17			
12					
13					
14					
15					
16					
17					
18					
19					

Upon execution, the formula returns **7**, indicating that there are 7 rows with recorded values in the Points column, while the remaining 3 rows are currently blank. This confirms the presence of data in the majority of the rows within the selected range.

Example 2: Counting Rows with No Value (Blanks)

Next, we focus on identifying data gaps. It is often necessary to know exactly how many entries are missing information, which is critical for assessing data quality and planning follow-up collection efforts. For this purpose, we use the specialized function `COUNTBLANK`.

The `COUNTBLANK` function is the most direct and efficient way to count empty cells within a range. Unlike `COUNTIF`, it requires no explicit criterion, simplifying the formula structure significantly. We apply this function directly to the range `B2:B11`.

=COUNTBLANK(B2:B11)

The following screenshot illustrates how this straightforward formula is entered into a cell to obtain the count of empty rows:



The result clearly shows that there are **3** rows with no value in the Points column. When combined with Example 1's result (7 non-blanks), the total number of rows (7 + 3 = 10) corresponds correctly to the specified range `B2:B11`.

Example 3: Counting Rows with a Specific Value

Finally, we address the need to count specific occurrences. Suppose we are interested in determining how many participants achieved a score of exactly `8` in the Points column. This task requires the use of the `COUNTIF` function, specifying the exact value we wish to match as the criterion.

When using `COUNTIF` to match a specific number, the number itself acts as the criterion. We apply

the formula to the range `B2:B11` and set the criterion to `"8"`. Note that even though 8 is a number, placing it in quotes is standard practice for criterion definition in spreadsheet functions, though sometimes optional for simple numeric matching.

=COUNTIF(B2:B11, "8")

Observe the application of this specific counting requirement in the following screenshot:



The output reveals that there are exactly **3** rows where the value in the Points column is `8`. This ability to count exact matches is invaluable for frequency distribution analysis and targeted data extraction.

Additional Resources for Data Management

The techniques detailed above form the foundation for advanced conditional counting in Google Sheets. For tasks requiring multiple conditions or more complex criteria, consider exploring functions such as **COUNTIFS** or **QUERY**. Understanding how to manage and count your data effectively ensures accuracy in your reports and enhances your overall spreadsheet proficiency.

The following tutorials explain how to perform other common operations essential for efficient data

handling and statistical analysis in spreadsheet software: